Nagios Installation and Configuration

Notes:

- * Commands preceded with "\$" imply that you should execute the command as a general user not as root.
- * Commands preceded with "#" imply that you should be working as root.
- * Commands with more specific command lines (e.g. "RTR-GW>" or "mysql>") imply that you are executing commands on remote equipment, or within another program.

Exercises

PART IV

Adding Parent Relationships

Each item is a child of either a switch or a router in our classroom, EXCEPT for your gateway router (rtrX) and the other members of your group. We are now going to add a "parents" statement for each device we have configured.

If you are unsure of the parent relationships you can look at our classroom Network Diagram. Remember, the parent relationships are from the point of view of your Nagios instance running on your pc.

```
1. Adding Parents to switches.cfg
_____
       $ cd /etc/nagios3/conf.d
       $ sudo editor switches.cfg
Update the entry:
define host {
   use
           generic-host
   Backbone Switch address 10.10 0 000
}
to be
define host {
             generic-host
   use
   host_name sw
            Backbone Switch
   alias
   address 10.10.0.253 parents rtrX
}
```

Where "rtrX" is the gateway router for your group. I.E., for group 1 you would use "rtr1", for group 2, "rtr2" and so forth.

Save and exit from the file.

```
2. Adding Parents to routers.cfg
_____
        $ sudo editor routers.cfg
For each entry we will add a "parents" line. So, for the gw-rtr definition at
the top of the file this should now look like:
define host {
   use
               generic-host
   host_name gw-rtr
   alias
               Classrooom Gateway Router
   address
              10.10.0.254
   parents
               sw
}
For all the remaining rtrX entries you should, also, add a line that says:
   parents
               SW
EXCEPT For the rtrX entry for your group. There should be NO PARENTS entry. If you
have an entry for "apl" (classroom wireless access point), then the parents entry is,
also, "sw" - same as the other routers.
So, if you are in group 2, then the entries for groups 1, 2 and 3 would look like:
define host {
               generic-host
   use
   host_name rtr1
   alias
               Group 1 Router
   address 10.10.1.254 parents sw
}
define host {
   use
               generic-host
   host_name rtr2
   alias Group 2 Router address 10.10.2.254
}
define host {
   use
               generic-host
   host_name rtr3
   alias
               Group 3 Router
   address 10.10.3.254 parents sw
```

Update the rest of the file correctly and then save and exit from the file.

3. Adding Parents to pcs.cfg

}

For all the PC entries you should add a "parents" line that has the router

```
for that PC's group. For the noc the parent is the core switch or "sw"
#
# Classroom NOC
define host {
   use generic-host
   host_name noc
   alias Workshop NOC machine address 10.10.0.250 parents sw
}
For PCs in Group 1 entries look like:
# Group 1
define host {
   use
               generic-host
   host_name pcl
   alias pcl
address 10.10.1.1
parents rtrl
}
define host {
   use
               generic-host
   host_name pc2
   alias pc2
address 10.10.1.2
parents rtr1
}
etcâ
Do this for all the PCs in the remaining groups. I.E., pc5 in Group 2 has
a parents statement of:
     parents rtr2
BUT, FOR THE 4 ENTRIES FOR THE PCS IN YOUR GROUP DO NOT ADD ANY PARENTS STATEMENT!
REPEAT - THE PCS IN YOUR GROUP DO NOT HAVE ANY PARENT ENTRY!
Save and exit from the file.
4. Restart Nagios and See the Updated Status Map
_____
        $ sudo service nagios3 restart
```

If you have errors, fix these and try restarting again.

Open a web browser to http://pcN.ws.nsrc.org/nagios3 and click on the "Map" link on the left. Your map should now look quite different. You should see a map that represents the Nagios world point of view from your machine.

PART V Create More Host Groups

- O. In the web view, look at the pages "Hostgroup Overview", "Hostgroup Summary", "Hostgroup Grid". This gives a convenient way to group together hosts which are related (e.g. in the same site, serving the same purpose).
- 1. Update /etc/nagios3/conf.d/hostgroups_nagios2.cfg
 - For the following exercises it will be very useful if we have created or update the following hostgroups:

debian-servers routers switches

If you edit the file /etc/nagios3/conf.d/hostgroups_nagios2.cfg you will see an entry for debian-servers that just contains localhost. Update this entry to include all the classroom PCs, including the noc (this assumes that you created a "noc" entry in your pcs.cfg file). Remember to skip your PC entry as it is represented by the localhost entry.

\$ sudo editor /etc/nagios3/conf.d/hostgroups_nagios2.cfg

Update the entry that says:

So that the "members" parameter contains something like this. Use your classroom network diagram to confirm the exact number of machines and names in your workshop.

members localhost,pc1,pc2,pc3,pc4,pc5,pc6,pc7,pc8,pc9,pc10,pc11,pc12, pc13,pc14,pc15,pc16,pc17,pc18,pc19,pc20,pc21,pc22,pc23,pc24,pc pc26,pc27,pc28,pc29,pc30,pc31,pc32,pc33,pc34,pc35,pc36

Be sure that the end of the line has a "\" to indicate a new line. Otherwise you will get an error when you go to restart Nagios. Remember that your own PC is "localhost", so skip your pc entry.

- Once you have done this, add one more host group for our classroom switch(es). If there is more than just one switch (sw.ws.nsrc.org) include this on the members line below, otherwise the entry at the end of the hostgroups_nagios2.cfg file should look like (COPY and PASTE):

```
define hostgroup {
       hostgroup_name switches
               alias Classroom Switches members sw
       }
      - When you are done be sure to verify your work and restart Nagios.
2. Go back to the web interface and look at your new Host Groups in Nagios.
PART VI
Extended Host Information ("making your graphs pretty")
_____
1. Update extinfo_nagios2.cfg
   - If you would like to use appropriate icons for your defined hosts in
     Nagios this is where you do this. We have the three types of devices:
     Cisco routers
     Cisco switches
     Ubuntu servers
     There is a fairly large repository of icon images available for you to
     use located here:
     /usr/share/nagios/htdocs/images/logos/
     these were installed by default as dependent packages of the nagios3
     package in Ubuntu. In some cases you can find model-specific icons for
     your hardware, but to make things simpler we will use the following
     icons for our hardware:
     /usr/share/nagios/htodcs/images/logos/base/debian.*
     /usr/share/nagios/htdocs/images/logos/cook/router.*
      /usr/share/nagios/htdocs/images/logos/cook/switch.*
   - The next step is to edit the file /etc/nagios3/conf.d/extinfo_nagios2.cfg
     and tell nagios what image you would like to use to represent your devices.
   $ sudo editor /etc/nagios3/conf.d/extinfo_nagios2.cfg
     Here is what an entry for your routers looks like (there is already an entry
     for debian-servers that will work as is). Note that the router model (3600)
     is not all that important. The image used represents a router in general.
define hostextinfo {
       hostgroup_name routers
       icon_image_alt     Cisco Routers (7200)
```

vrml_image router.png
statusmap_image cook/router.gd2

}

Note how we can simply use "hostgroup_name routers" as this has already been defined in the file hostgroups_nagios2.cfg. This makes configuring multiple, like items much simpler.

Now add an entry for your switches. Once you are done check your work and restart Nagios. Take a look at the Status Map in the web interface (Map link on the left). It should be much nicer, with real icons instead of question marks for most items.

PART VII Create Service Groups

- 1. Create service groups for ssh and http for each set of pcs.
 - The idea here is to create three service groups. Each service group will be for a quarter of the classroom. We want to see these PCs grouped together and include status of their ssh and http services. To do this edit and create the file:

```
$ cd /etc/nagios3/conf.d (just to be sure)
$ sudo editor servicegroups.cfg
```

Here is a sample of the service group for group 1:

```
define servicegroup {
    servicegroup_name group1-services
    alias group 1 services
    members pc1,SSH,pc1,HTTP,pc2,SSH,pc2,HTTP,pc3,SSH,pc3,HTTP,pc4,SSH,pc4
}
```

- Note that if the members line is too long you can use the "\" at the end to create a new line of members just below.
- Note that "SSH" and "HTTP" need to be uppercase as this is how the service_description written in the file /etc/nagios3/conf.d/services_nagios2.cfg
- You should create an entry for other groups of servers too.
- CRITICAL When you create an entry for your group remember to use "localhost" instead of your "pcN" name since you have only defined your pc as localhost in the file hostgroups_nagios2.cfg.
- Save your changes, verify your work and restart Nagios. Now if you click on the Service Groups menu item in the Nagios web interface you should see this information grouped together.

PART VIII Configure Guest Access to the Nagios Web Interface

- 1. You will edit the file /etc/nagios3/cgi.cfg to give read-only guest user access to the Nagios web interface.
 - By default Nagios is configured to give full r/w access via the Nagios web interface to the user nagiosadmin. You can change the name of this user, add other users, change how you authenticate users, what users have access to what resources and more via the cgi.cfg file.
 - First, lets create a "guest" user and password in the htpasswd.users

\$ sudo htpasswd /etc/nagios3/htpasswd.users guest

You can use any password you want (or none). A password of "guest" is not a bad choice.

- Next, edit the file /etc/nagios3/cgi.cfg and look for what type of access has been given to the nagiosadmin user. By default you will see the following directives (note, there are comments between each directive):

authorized_for_system_information=nagiosadmin authorized_for_configuration_information=nagiosadmin authorized_for_system_commands=nagiosadmin authorized_for_all_services=nagiosadmin authorized_for_all_hosts=nagiosadmin authorized_for_all_service_commands=nagiosadmin authorized_for_all_host_commands=nagiosadmin

Now let's tell Nagios to allow the "guest" user some access to information via the web interface. You can choose whatever you would like, but what is pretty typical is this:

authorized_for_system_information=nagiosadmin,guest authorized_for_configuration_information=nagiosadmin,guest authorized_for_system_commands=nagiosadmin authorized_for_all_services=nagiosadmin,guest authorized_for_all_hosts=nagiosadmin,guest authorized_for_all_service_commands=nagiosadmin authorized_for_all_host_commands=nagiosadmin

- Note we do not give the guest user access to system commands, service commands nor host commands.
- Once you make the changes, save the file cgi.cfg, verify your work and restart Nagios.
- To see if you can log in as the "guest" user you will need to clear the cookies in your web browser or open an alternate web browser if you have one. You will not notice any difference in the web interface. The difference is that a number of items that are available via the web interface (forcing a service/host check, scheduling checks, comments, etc.) will not work for the guest user.