

# Netdot exercise

## Network Management Topics

### Contents

<b>1</b>	<b>Introduction</b>	<b>2</b>
1.1	Goals . . . . .	2
1.2	Notes . . . . .	2
<b>2</b>	<b>Installation</b>	<b>2</b>
2.1	Download the Package . . . . .	2
2.2	Install dependencies: . . . . .	3
2.3	Initialize the site configuration: . . . . .	4
2.4	Install the application and initialize the database. . . . .	5
<b>3</b>	<b>Operation</b>	<b>5</b>
3.1	Log into the web interface . . . . .	5
3.2	Changing default passwords . . . . .	5
3.3	Discovering devices . . . . .	5
3.4	Finding a computer in your network . . . . .	7
3.5	Managing IP address space . . . . .	8
3.5.1	Create a container to include all the group subnets . . . . .	8
3.6	Polling devices . . . . .	9
<b>4</b>	<b>More information</b>	<b>9</b>

# 1 Introduction

The Network Documentation Tool (Netdot) is an open source software designed to help network administrators collect, organize and maintain network documentation. Netdot is actively developed at the University of Oregon.

## 1.1 Goals

In these exercises we will install Netdot and demonstrate some of its most important features.

## 1.2 Notes

- Commands preceded with “\$” imply that you should execute the command as a general user - not as root.
- Commands preceded with “#” imply that you should be working as root.
- Commands with more specific command lines (e.g. “rtrX>” or “mysql>”) imply that you are executing commands on remote equipment, or within another program.

# 2 Installation

*Netdot may already be installed in your PC. Ask the instructor.*

Log in to your virtual machine as the sysadm user and make sure your machine is up-to-date with the rest of the class:

```
$ sudo apt-get install snmp snmp-mibs-downloader snmpd cacti smokeping \
nagios3 joe postfix
```

## 2.1 Download the Package

First check if it's available in your classroom's NOC server:

```
$ cd
$ wget http://noc.ws.nsrc.org/downloads/netdot-1.0.4.tar.gz
```

If not, try from the official site:

```
$ wget http://netdot.uoregon.edu/pub/dists/netdot-1.0.4.tar.gz
```

Unpack the tarball:

```
$ tar xzvf netdot-1.0.4.tar.gz
$ cd netdot-1.0.4
```

## 2.2 Install dependencies:

```
$ sudo apt-get install build-essential
$ sudo make apt-install
```

Which RDBMS do you plan to use as backend: [mysql|Pg]? mysql

We need to add a temporary repository of Netdot dependencies until all packages are in Debian/Ubuntu official repositories.

Would you like to continue? [y/n] y

This will download a lot of packages. Be patient.

(If you had not installed mysql-server, you'll be asked for a DBA password. Ask the instructor for the Mysql root password).

Say yes here:

We will install the MIB files now. Continue? [y/n] y

If you see this prompt, then answer yes:

A new /etc/snmp/snmp.conf needs to be installed to point to the newly installed MIB files. The current file will be backed up. Continue? [y/n] y

At the end of the installation you will see a list of Perl modules that have been installed (OK). If any did not install you will see "MISSING".

---

**NOTE** If more than two packages show as MISSING, do not continue. Ask your instructor for help. Probably you will need to go back and repeat the last section (`sudo make apt-install`) and look for errors.

---

If one or two packages are missing, type:

```
$ sudo make installdeps
```

```
Which RDBMS do you plan to use as backend: [mysql|Pg]? mysql
```

You will now see three questions concerning CPAN setup to download the missing PERL dependency. Answer like this:

```
Would you like to configure as much as possible automatically? [yes] yes
```

```
What approach do you want? (Choose 'local::lib', 'sudo' or 'manual')  
[local::lib] <ENTER>
```

```
Would you like me to automatically choose some CPAN mirror  
sites for you? (This means connecting to the Internet) [yes]
```

If you still see missing dependencies do:

```
$ sudo make installdeps
```

Until you don't see any more missing dependencies.

This will try to install the missing modules using the CPAN archive. At the end, all the modules should show "ok".

### 2.3 Initialize the site configuration:

```
$ cd ~/netdot-1.0.4/  
$ cp etc/Default.conf etc/Site.conf  
$ editor etc/Site.conf
```

Find and change the following values:

```
NETDOTNAME => 'pcX.ws.nsrc.org',  
DB_DBA_PASSWORD => '(the password you used when installing mysql)',  
DEFAULT_SNMPCOMMUNITIES => ['NetManage', 'public'],  
NMS_DEVICE => 'pcX.ws.nsrc.org',  
DEFAULT_DNSDOMAIN => 'ws.nsrc.org',  
DEVICE_NAMING_METHOD_ORDER => [ 'sysname', 'snmp_target' ],
```

Save and exit from the file.

## 2.4 Install the application and initialize the database.

```
$ sudo make installdb
$ sudo make install APACHEUSER=www-data APACHEGROUP=www-data
$ sudo ln -s /usr/local/netdot/etc/netdot_apache2_local.conf \
/etc/apache2/conf.d/
$ sudo service apache2 graceful
```

Install the cron jobs for automated tasks

```
$ sudo cp netdot.cron /etc/cron.d/netdot
```

## 3 Operation

### 3.1 Log into the web interface

In your browser, go to:

```
http://pcX.ws.nsrc.org/netdot
```

Log in with username: admin and password: admin

### 3.2 Changing default passwords

Netdot comes with three default user accounts. You should change the default passwords on those.

Go to the “Contacts” tab, then search for “Admin”. You should see the details for the Admin user. Click on [edit], and find the Password field. Type the password you used to log in to your PC, then click on the “Update” button.

Repeat the same steps for the other default users:

- operator
- guest

### 3.3 Discovering devices

If you have not done so yet, configure SNMP on your PC and your router.

*Ask the instructor to provide you with instructions for configuring SNMP on Cisco routers and Linux*

Now back to Netdot. Let’s create a file with all the devices in the lab network that respond to SNMP:

```
$ editor /home/sysadm/discoverme.txt
```

Copy and paste the following list:

```
gw.ws.nsrc.org NetManage  
s1.ws.nsrc.org NetManage  
sw.ws.nsrc.org NetManage  
rtr1.ws.nsrc.org NetManage  
rtr2.ws.nsrc.org NetManage  
rtr3.ws.nsrc.org NetManage  
rtr4.ws.nsrc.org NetManage  
rtr5.ws.nsrc.org NetManage  
rtr6.ws.nsrc.org NetManage  
rtr7.ws.nsrc.org NetManage  
rtr8.ws.nsrc.org NetManage  
rtr9.ws.nsrc.org NetManage  
pc1.ws.nsrc.org NetManage  
pc2.ws.nsrc.org NetManage  
pc3.ws.nsrc.org NetManage  
pc4.ws.nsrc.org NetManage  
pc5.ws.nsrc.org NetManage  
pc6.ws.nsrc.org NetManage  
pc7.ws.nsrc.org NetManage  
pc8.ws.nsrc.org NetManage  
pc9.ws.nsrc.org NetManage  
pc10.ws.nsrc.org NetManage  
pc11.ws.nsrc.org NetManage  
pc12.ws.nsrc.org NetManage  
pc13.ws.nsrc.org NetManage  
pc14.ws.nsrc.org NetManage  
pc15.ws.nsrc.org NetManage  
pc16.ws.nsrc.org NetManage  
pc17.ws.nsrc.org NetManage  
pc18.ws.nsrc.org NetManage  
pc19.ws.nsrc.org NetManage  
pc20.ws.nsrc.org NetManage  
pc21.ws.nsrc.org NetManage  
pc22.ws.nsrc.org NetManage  
pc23.ws.nsrc.org NetManage  
pc24.ws.nsrc.org NetManage  
pc25.ws.nsrc.org NetManage  
pc26.ws.nsrc.org NetManage  
pc27.ws.nsrc.org NetManage  
pc28.ws.nsrc.org NetManage  
pc29.ws.nsrc.org NetManage
```

```
pc30.ws.nsrc.org NetManage
pc31.ws.nsrc.org NetManage
pc32.ws.nsrc.org NetManage
pc33.ws.nsrc.org NetManage
pc34.ws.nsrc.org NetManage
pc35.ws.nsrc.org NetManage
pc36.ws.nsrc.org NetManage
```

Now, tell Netdot to discover those devices:

```
$ cd /usr/local/netdot
$ sudo bin/updatedevices.pl -E /home/sysadm/discoverme.txt -IAF
```

When that is done, go to the web interface and navigate to

Management -> Devices

Leave the search box empty, and click on the “Find” button.

You should see all the discovered devices in that list. Go to the link for your group’s router (e.g. rtrX.ws.nsrc.org)

- Navigate to all the tabs: Basic, Interfaces, Modules, IP Info, etc. Netdot allows you to augment the information gathered from the device with details entered manually.
- In the ARP section, you should see one entry with a timestamp. Click on that entry. You should see a table associating IP addresses with MAC addresses. This is the ARP table discovered from rtr1. You should see your PC’s IP address and MAC address.

### 3.4 Finding a computer in your network

- Obtain the MAC address from your laptop (or desktop). Copy it in the clipboard.
- In the Netdot web interface, go to Management -> Devices
- Paste your MAC address and hit ENTER

Netdot will show you which devices were seeing that MAC address the last time that it discovered the network.

## 3.5 Managing IP address space

Go to Management -> Address Space

You should see a list of private IP blocks (from RFC-1918). These come pre-installed in Netdot.

Click on 10.0.0.0/8

You will see a list of discovered IP blocks, which are marked as “Subnets”. These were found in routers.

- Click on 10.10.1.0/24.
- Click on [edit]
- In the Description field, type “Group 1 PCs”
- Click “Save”

### 3.5.1 Create a container to include all the group subnets

In the section called “Address Space Tasks” on top, click on the “[new]” button and enter the following:

- IP/Prefix: 10.10.0.0/16
- Owner: click on [new].
- In the new “Entity” window, enter:
- Name: NSRC Lab
- Insert button, then [close]
- Used by: (leave blank)
- Status: Container
- Description: NSRC lab student networks
- Save

You should now see the new Container page. It shows a graphical representation of the /16 block. All the existing subnets are shown in red. The green space represents unused or available address space.

- On the top of the graph there is a section called “Zoom: set one row equal to” Select /24 from the drop-down menu. Each row now represents a /24 block
- Click on [Tree View] to see a tree graph view of the IP hierarchy



### 3.6 Polling devices

Periodically you will want to connect again to your routers and switches to fetch their routing tables, forwarding tables etc. You can run the command which does this:

```
$ sudo /usr/local/netdot/bin/updatedevices.pl -DIFAT
```

- -D: poll all devices already in the database
- -I: get device info (e.g. sysName)
- -F: get switch forwarding tables
- -A: get router ARP tables
- -T: re-calculate the topology

To avoid having to run this by hand, you can install a crontab which will do it automatically at set times of day. We installed the crontab file in `/etc/cron.d` previously. If you look in `/etc/cron.d/netdot` you will see that this command executes once each hour by default.

## 4 More information

[Official Netdot Website](#)