

Fiber Optic Construction & Termination

Jeff Hite
University of Oregon/NSRC
jeffh@uoregon.edu

This document is a result of work by the Network Startup Resource Center (NSRC at <http://www.nsrc.org>). This document may be freely copied, modified, and otherwise re-used on the condition that any re-use acknowledge the NSRC as the original source.



UNIVERSITY OF OREGON



Campus Network Plant Construction

- Fiber Selection
- UTP Copper
- Pathway Construction
- Installation Guidelines
- Termination



UNIVERSITY OF OREGON



Fiber Package Selection

- Use outdoor rated cable between buildings
 - Armored Loose tube (to protect against rodents)
 - Un-armored loose tube in conduit if rodents not an issue
 - Indoor/Outdoor tight buffer if possible
- Use indoor rated cabling inside buildings
 - tight buffer
- Standardize Connectors
 - Multi mode: ST or SC (epoxy or hot melt)
 - Single mode: SC or LC (fusion Splice factory UPC pigtail) (Can hand polish for short runs <2 km)




UNIVERSITY OF OREGON



Fiber Optic Cable Construction

- Fiber has bend radius issues
- Keep bends $\geq 10x$ cable diameter



UNIVERSITY OF OREGON



Fiber Optic Cable Construction

- Leave slack loops, usually 10m per location



UNIVERSITY OF OREGON



Outdoor loops in Thailand



UNIVERSITY OF OREGON



Small Vault Slack Loop



UNIVERSITY OF OREGON



Closet Slack Loops



UNIVERSITY OF OREGON




Conduit Construction

- Sizing Pathway
 - Bigger is better, allows installation of more than one cable package per conduit
 - Install additional runs of pathway (100% more than you need today)
 - Plan for the future, think of strand count
 - Install a pull-rope with the fiber
 - Label conduits if possible
- Identifying Fiber
 - Label at each end, strand count, type and destination
 - Label slack loops, Where from? Where to?



Conduit Construction Hints

- For cable installed in underground conduit:
 - No more than 200m between pull points
 - Reduce distance by 50m for every 90 degrees of bend
 - Do not exceed 270 degrees
 - Survey the site and do the arithmetic
 - Very Important!



Fiber Color Codes

(May vary by region)

Blue	Red
Orange	Black
Green	Yellow
Brown	Violet
Slate (Gray)	Rose (Pink)
White	Aqua (Light Blue)

After the 12th Fiber or Tube a black stripe is added to differentiate between groups.



UNIVERSITY OF OREGON



Construction Guidelines for Copper and Fiber Optic installations



UNIVERSITY OF OREGON



Instructions to Contractors

- Please refer to the web site for this workshop to retrieve document that gives complete instructions to contractors for
 - Category 5e cabling
 - Fiber optic cabling
 - Installation of underground conduit and vaults
- Download and edit this document to meet your needs.
 - http://203.159.31.222/CND/01.3_Cabling_Systems_Specifications.doc



UNIVERSITY OF OREGON




Modular UTP Jack



UNIVERSITY OF OREGON




Modular Jack Rear View



UNIVERSITY OF OREGON



48-Port M6 Patch Panel




UNIVERSITY OF OREGON




Unshielded Twisted Pair Cable (UTP)

- Always terminate in Jack Panel
- Labeling is a key to reduce work later
- Pull more than one cable



110 Termination Patch Panel



UNIVERSITY OF OREGON



110 Termination Technique



UNIVERSITY OF OREGON



Fiber Package Selection

- Use outdoor rated cable between buildings
 - Armored Loose tube (to protect against rodents)
 - Un-armored loose tube in conduit if rodents not an issue
 - Indoor/Outdoor tight buffer if possible
- Use indoor rated cabling inside buildings
 - tight buffer
- Standardize Connectors
 - Multi mode: ST or SC (epoxy or hot melt)
 - Single mode: SC or LC (fusion Splice factory UPC pigtail) (Can hand polish for short runs <2 km)



UNIVERSITY OF OREGON



Fiber Panel Connectors & Patch Cords

- Connectors
 - Many types of connectors are available
 - Choose connectors to differentiate fiber types
 - Very Important!
 - ST connectors are suitable for MM
 - SC connectors are suitable for SM
 - LC are useable for both types

Patch Cords


- OM1 are generally Orange but other colors are used
- OM2 OM3 OM4 use Aqua
- OS2 cords are exclusively yellow



UNIVERSITY OF OREGON



ST & SC Fiber Optic Connectors



UNIVERSITY OF OREGON




LC Connector



UNIVERSITY OF OREGON




Duplex LC Connector




UNIVERSITY OF OREGON




Connector tip




- Flat: air between surfaces, back reflection -14dB



- Physical contact: slanted end, no air, back reflection -40dB



- Ultra Polish Connector: more polishing, back reflection -55dB



- Angled Polish Connector: back reflection -70dB, analog signal



UNIVERSITY OF OREGON



Fiber Patch Panel



UNIVERSITY OF OREGON





SC Connector Panel




ST Connector Panel



UNIVERSITY OF OREGON




Relay Racks



UNIVERSITY OF OREGON



Indoor Fiber Packages



UNIVERSITY OF OREGON




Outdoor Loose Tube Armored Cable



UNIVERSITY OF OREGON




96 Fiber Loose Tube Outdoor Non-Armored




UNIVERSITY OF OREGON



Loose Tube vs. Tight Buffer



- Loose Tube: several fibers 250 micron in a buffer tube, gel filling, more compact, fragile, outdoor.



- Tight Buffer: one fiber in a 0.9mm buffer, no gel, bigger, sturdier, in/outdoor.



UNIVERSITY OF OREGON


Break Out Kits (Furcation)



UNIVERSITY OF OREGON




Types of Optical Fiber



UNIVERSITY OF OREGON

Fiber Cable Construction



UNIVERSITY OF OREGON

Fiber Termination Techniques

- Hand Polishing (Epoxy or Hot Melt)
- Mechanical connectors (do not use)
- Fusion Splicing



UNIVERSITY OF OREGON



Fiber in Ferrule – no back light

Top View





Photo Image




* Ferrule not visible in photo



UNIVERSITY OF OREGON




MM Fiber in Ferrule – Back Lit



UNIVERSITY OF OREGON

MM fiber with 100x microscope




- Manually polished MM connector shows many defects whereas industrial one is perfect.



UNIVERSITY OF OREGON



Single Mode Fiber - Back Lit



UNIVERSITY OF OREGON



Questions?

This document is a result of work by the Network Startup Resource Center (NSRC at <http://www.nsrc.org>). This document may be freely copied, modified, and otherwise re-used on the condition that any re-use acknowledge the NSRC as the original source.



UNIVERSITY OF OREGON



Demo of fiber optic termination

This part is for reference only.



UNIVERSITY OF OREGON



The tools we use




- The stripper is used to remove the buffer and coating.



UNIVERSITY OF OREGON



The tools we use



- The plate and the rubber pad provide a flat, smooth and soft surface for polishing.



UNIVERSITY OF OREGON



The tools we use

5 micron

polishing film



1 micron
polishing film

- Polishing Film, this is coated with ceramic or diamond .



UNIVERSITY OF OREGON



The tools we use



- The cleaning tape is used with terminated connectors.

- Gently brush the ferule with figure of 8 motions, on a clean portion of tape.




UNIVERSITY OF OREGON



The tools we use

x100 illuminated microscope



- Never flash the laser to the eye.


Laser cable tester



UNIVERSITY OF OREGON



The tools we use



- The scribe is sharper than a razor blade; always recap it.



UNIVERSITY OF OREGON



The tools we use



- Use the fiber disposal bottle to dispose of pieces of core fiber.

- Stripped fiber is very sharp and can damage your eyes.



UNIVERSITY OF OREGON



Where to buy the tools?

- Fiber Network Tools (buy online) <http://www.fnttools.com/store/pc/home.asp>
- Specialized Products Company (buy online) <http://www.specialized.net/Specialized/FIBER-OPTIC-5768.aspx>
- Ellsworth Adhesives Thailand (glue) <http://www.ellsworth.co.th/product/surface/surface/1672.html>



UNIVERSITY OF OREGON



Termination Procedure


- The following slides show the termination procedure for an ST connector



UNIVERSITY OF OREGON



Prepare the connector




- Slide the plastic tube and the bend protector on the fiber.



UNIVERSITY OF OREGON



Remove the jacket




- Use scissors to score jacket.
- Plan enough length to install in patch panel. Usually .5 meter is sufficient.



UNIVERSITY OF OREGON



Make a pull string



- Weave the yarn to make a pull string.
- It is useful to secure the fiber in the cabinet.



UNIVERSITY OF OREGON



Strip off the buffer

- Use middle slot of the stripper tool to remove the plastic buffer.



UNIVERSITY OF OREGON



Strip off the coating





- Use the smaller slot of the stripper tool to remove the coating.
- You have stripped to 125 micron fiber, dispose the waste properly.



UNIVERSITY OF OREGON



FO with and without coating



- Before and after you remove the coating.
- Without coating the fiber is thinner.



UNIVERSITY OF OREGON



Prepare the glue



- Fill the ferule with glue (red bottle).
- Be careful with the glue.



UNIVERSITY OF OREGON



Insert the fiber




- Gently insert the fiber through the connector you will see it come out of the ferrule.



UNIVERSITY OF OREGON



Push the plastic tube




- Push the plastic tube in place, inside the connector and ferule.



UNIVERSITY OF OREGON



Finish gluing




- Add the catalyst (white bottle) at top of plastic tube and at the connector where the fiber protrudes from the ferrule.



UNIVERSITY OF OREGON



Scribe the excess fiber




- Use the scribe tool to gently score around the fiber. After scoring pull the fiber straight up and dispose in the fiber trash can.



UNIVERSITY OF OREGON



Note the stump




- With the magnifier you can clearly see the stump made by the glue and the core.



UNIVERSITY OF OREGON



Polish on 5 micron




- Hold the puck only.
- Make 50 figure 8's on 5 micron (black) polishing film.
- Use the plate and pad as support.



UNIVERSITY OF OREGON



Polish on 1 micron



- Use the 1 micron (green) polishing film. Hold firmly on the connector and press down. Make 50 figures of 8. use plate and pad.



UNIVERSITY OF OREGON



Note the figure 8's




- During the process the polishing film shows marks in shape of 8.
- The film can be reused a couple of times.



UNIVERSITY OF OREGON



Check your work




- Use the laser tool to verify that the light can pass through the fiber and connectors.
- Do not point the laser directly into the eye.



UNIVERSITY OF OREGON



Check with the microscope



- Manually polished MM connector (left) and factory machine polish (right).
- Note the difference.



UNIVERSITY OF OREGON



Thank You and Good Luck in
Building your Network Plant!



UNIVERSITY OF OREGON

