Introduction to Internet Mail

***Abridged & Updated* by Hervey Allen**

Noah Sematimba

Based on Materials by Philip Hazel

Mail agents

- MUA = Mail User Agent
- Interacts directly with the end user
  Pine, MH, Elm, mutt, mail, Eudora, Marcel, Mailstrom,
  Mulberry, Pegasus, Simeon, Netscape, Outlook, ...
- Multiple MUAs on one system - end user choice

- MTA = Mail Transfer Agent
- Receives and delivers messages
  Sendmail, Smail, PP, MMDF, Charon, Exim, qmail, Postfix, ...
- One MTA per system - sysadmin choice

Message format (1)

```
From: Philip Hazel <ph10@cus.cam.ac.uk>
To: Julius Caesar <julius@ancient-rome.net>
Cc: Mark Anthony <MarkA@cleo.co.uk>
Subject: How Internet mail works

Julius,
  I'm going to be running a course on ...
```

- Format was originally defined by RFC 822 in 1982
- Now superseded by RFC 2822
- Message consists of
  Header lines
  A blank line
  Body lines

Message format (2)

- An address consists of a *local part* and a *domain*
  julius@ancient-rome.net

- A basic message body is unstructured

- Other RFCs (MIME, 2045) add additional headers which define structure for the body

- MIME supports attachments of various kinds and in various encodings

- Creating/decoding attachments is the MUA's job



Authenticating senders

- Embedded MUA uses inter-process call to send to MTA
  - May use pipe, file, or internal SMTP over a pipe
  - MTA knows the identity of the sender
  - Normally inserts *Sender:* header if differs from *From:*
- Freestanding MUA uses SMTP to send mail
  - MTA cannot easily distinguish local/remote clients
  - No authentication in basic protocol
  - AUTH command in extended SMTP
  - Use of security additions (TLS/SSL)
  - MUA can point at any MTA whatsoever
  - Need for relay control
  - Host and network blocks

A message in transit (1)

- Headers added by the MUA before sending

```
From: Philip Hazel <ph10@cus.cam.ac.uk>
To: Julius Caesar <julius@ancient-rome.net>
cc: Mark Anthony <MarkA@cleo.co.uk>
Subject: How Internet mail works
Date: Fri, 10 May 2002 11:29:24 +0100 (BST)
Message-ID: <Pine.SOL.3.96.990117111343.
  19032A-100000@taurus.cus.cam.ac.uk>
MIME-Version: 1.0
Content-Type: TEXT/PLAIN; charset=US-ASCII

Julius,
  I'm going to be running a course on ...
```

A message in transit (2)

- Headers added by MTAs

```
Received: from taurus.cus.cam.ac.uk
  ([192.168.34.54] ident=exim)
  by mauve.csi.cam.ac.uk with esmtp
  (Exim 4.00) id 101qxX-00011X-00;
  Fri, 10 May 2002 11:50:39 +0100
Received: from ph10 (helo=localhost)
  by taurus.cus.cam.ac.uk with local-smtp
  (Exim 4.10) id 101qin-0005PB-00;
  Fri, 10 May 2002 11:50:25 +0100
From: Philip Hazel <ph10@cus.cam.ac.uk>
To: Julius Caesar <julius@ancient-rome.net>
cc: Mark Anthony <MarkA@cleo.co.uk>
...
```

A message in transit (3)

- A message is transmitted with an *envelope*:
  ```
  MAIL FROM:<ph10@cus.cam.ac.uk>
  RCPT TO:<julius@ancient-rome.net>
  ```
- The envelope is separate from the RFC 2822 message
- Envelope (RFC 2821) fields need not be the same as the header (RFC 2822) fields
- MTAs are (mainly) concerned with envelopes
  Just like the Post Office...
- Error ("bounce") messages have null senders
  ```
  MAIL FROM:<>
  ```

An SMTP session (1)

```
telnet relay.ancient-rome.net 25
220 relay.ancient-rome.net ESMTP Exim ...
EHLO taurus.cus.cam.ac.uk
250-relay.ancient-rome.net ...
250-SIZE 10485760
250-PIPELINING
250 HELP
MAIL FROM:<ph10@cus.cam.ac.uk>
250 OK
RCPT TO:<julius@ancient-rome.net>
250 Accepted
DATA
354 Enter message, ending with "."
Received: from ...
     (continued on next slide)
```

An SMTP session (2)

```
From: ...
To: ...
etc...
.
250 OK id=10sPdr-00034H-00
quit
221 relay.ancient-rome.net closing conn...
```

SMTP return codes

- 2*xx* OK
- 3*xx* send more data
- 4*xx* temporary failure
- 5*xx* permanent failure

Use of the DNS for email (1)

- Two DNS record types are used for routing mail
- *Mail Exchange* (MX) records map mail domains to host names, and provide a list of hosts with preferences:
  ```
  hermes.cam.ac.uk. MX 5 green.csi.cam.ac.uk.
                    MX 7 ppsw3.csi.cam.ac.uk.
                    MX 7 ppsw4.csi.cam.ac.uk.
  ```
- *Address* (A) records map host names to IP addresses:
  ```
  green.csi.cam.ac.uk.  A  131.111.8.57
  ppsw3.csi.cam.ac.uk.  A  131.111.8.38
  ppsw4.csi.cam.ac.uk.  A  131.111.8.44
  ```

Use of the DNS for email (2)

- MX records were added to the DNS after its initial deployment
- Backwards compatibility rule:
  If no MX records found, look for an A record, and if found, treat as an MX with 0 preference
- MX records were invented for gateways to other mail systems, but are now heavily used for handling generic mail domains

Common DNS errors

- Final dots missing on RHS host names in MX records
- MX records point to aliases instead of canonical names
  This should work, but is inefficient and deprecated
- MX records point to non-existent hosts
- MX records contain an IP address instead of a host name on the righthand side
  Unfortunately some MTAs accept this
- MX records do not contain a preference value
- Some broken name servers give a server error when asked for a non-existent MX record

Routing a message

- Process local addresses
  Alias lists
  Forwarding files
- Recognize special remote addresses
  e.g. local client hosts
- Look up MX records for remote addresses
- If self in list, ignore all MX records with preferences greater than or equal to own preference
- For each MX record, get IP address(es)

Delivering a message

- Perform local delivery
- For each remote delivery
  Try to connect to each remote host until one succeeds
  If it accepts or permanently reject the message, that's it
- After temporary failures, try again at a later time
- Time out after deferring too many times
- Addresses are often sorted to avoid sending multiple copies

Checking incoming senders

- A lot of messages are sent with bad envelope senders
  - Misconfigured mail software
  - Unregistered domains
  - Misconfigured name servers
  - Forgers
- Forgery seems to be the largest category nowadays
- Many MTAs check the sender's domain
- It is harder to check the local part
  - Uses more resources, and can be quite slow
- Bounce messages have no envelope sender

Checking incoming recipients

- Some MTAs check each local recipient during the SMTP transaction
  - Errors are handled by the *sending* MTA
  - The receiving MTA avoids problems with bad senders
- Other MTAs accept messages without checking, and look at the recipients later
  - Errors are handled by the *receiving* MTA
  - More detailed error messages can be generated
- The current proliferation of forged senders has made the first approach much more popular

Relay control

- Incoming: From any host to specified domains
  - e.g. incoming gateway or backup MTA
- Outgoing: From specified hosts to anywhere
  - e.g. outgoing gateway on local network
- From authenticated hosts to anywhere
  - e.g. travelling employee or ISP customer connected to remote network
- Encryption can be used for password protection during authentication
- Authentication can also be done using certificates

Policy controls on incoming mail

- Block known miscreant hosts and networks
  - Realtime Blackhole List (RBL), Dialup list (DUL), etc.
  - **http://mail-abuse.org** (now a charged service) and others
- Block known miscreant senders
  - Not as effective as it once was for SPAM
- Refuse malformed messages
- Recognize junk mail
  - Discard
  - Annotate